


Si PIN photodiode

S4349

Quadrant Si PIN photodiode



S4349 is a quadrant Si PIN photodiode having sensitivity in the UV to near IR spectral range. A quadrant element format allows position sensing such as for laser beam axis alignment.

Features

- Quadrant (2 × 2) element format
- Low cross-talk: 2 % Max.
- Wide spectral response range: 190 to 1000 nm
- High-speed response: $f_c=20$ MHz
- TO-5 metal package

Applications

- Laser beam axis alignment
- Position sensing

■ General ratings

Parameter	Symbol	Value	Unit
Window material	-	Quartz glass	-
Active area	A	○ 3.0/4 element	mm
Element gap	-	100	μm


■ Absolute maximum ratings

Parameter	Symbol	Value	Unit
Reverse voltage	V_R Max.	20	V
Operating temperature	T_{opr}	-20 to +60	°C
Storage temperature	T_{stg}	-55 to +80	°C

■ Electrical and optical characteristics ($T_a=25$ °C, per 1 element)


Parameter	Symbol	Condition	Typ.	Max.	Unit
Spectral response range	λ		190 to 1000	-	nm
Peak sensitivity wavelength	λ_p		720	-	nm
Photo sensitivity	S	$\lambda=\lambda_p$	0.45	-	A/W
Dark current	I_D	$V_R=5$ V	0.01	0.2	nA
Temperature coefficient of I_D	T_{CID}		1.12	-	times/°C
Cut-off frequency	f_c	$V_R=5$ V, $R_L=50$ Ω $\lambda=780$ nm, -3 dB	20	-	MHz
Terminal capacitance	C_t	$V_R=5$ V, $f=1$ MHz	25	-	pF
Noise equivalent power	NEP	$V_R=5$ V, $\lambda=\lambda_p$	4.0×10^{-15}	-	W/Hz ^{1/2}
Cross-talk	CL	$V_R=5$ V, $\lambda=780$ nm	-	2	%

■ Spectral response




KMPD80126EA

■ Photo sensitivity temperature characteristic




KMPD80127EA

■ Dark current vs. reverse voltage




KMPD80128EA

■ Terminal capacitance vs. reverse voltage



KMPD80129EA

■ Dimensional outline (unit: mm)



KMPDA0114EA

HAMAMATSU

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2006 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184, www.hamamatsu.com

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trépu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Twin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741